Product Datasheet

PET Dispensing Unit

A cost-effective solution for sub-dispensing of PET isotopes in a Grade A air environment, this stand-alone, self-contained unit is designed for safety, efficiency, and compliance. These units are available in 1000 mm, 1200 mm and 1500 mm widths.

- Solid surface worktop.
- Vertical grade A air downflow hood.
- Counter sunk 50 mm lead shielded waste safe to take sharps containers.
- Counter sunk 50 mm lead shielded dose calibrator housing.
- 50 mm lead shielded safe for the storage of calibration sources, etc.
- 13 Amp socket incorporated into the rear wall of the unit.
- Unshielded storage cupboard.



Key Features

Lead Shielding Options

Powder Coated Finish

Specifications

Description	Dimensions (H x W x D) (mm)	Base Unit Dimensions (H) (mm)
PET Dispensing Unit	2231 x 1000 x 760 approx.	900
PET Dispensing Unit	2231 x 1200 x 760 approx.	900
PET Dispensing Unit	2231 x 1500 x 760 approx.	900

Custom sizes and lead thicknesses available on request

Bright Technologies Ltd
Bri-Tec House, 1 Holbrook Close
Holbrook Commerce Park
Sheffield, S20 3FJ

E-mail: info@britec.net
Tel: +44 (0)114 251 1215

www.britec.net

Version 1.0 May 2026