Product Datasheet

Syringe Carrier

Ideal for transporting loaded syringes and/or small radioactive sources. All carriers are constructed from a steel stove enamelled box lined with lead. Lead thicknesses come in either 3 mm or 6 mm.

- The hinged lid is fitted with a front fixing catch which can be sealed for security.
- All carriers are supplied with a choice of fixed or pivoting handle.
  The pivoting handle is locked in the upright position when carried.
- All carriers are fitted with an internal, removable, rigid plastic (ABS) tray.
- The internal length of the carriers is designed to accept a full 10 ml syringe fitted with a 25 mm capped needle.
  100 mm handle clearance from lid.
- Mild steel (CR4) powder coated outer case.



Key Features

Lead Shielding Options

Powder Coated Finish

Specifications

Code	Description	Lead Thickness (mm)	Internal Dimensions (L x W x H) (mm)	External Dimensions (L x W x H) (mm)	Weight (kg)
4BT-SCBF3	Small Carrier, Fixed Handle	3	240 x 52 x 40	305 x 110 x 220	4.5
4BT-SCBP3	Small Carrier, Pivot Handle	3	240 x 52 x 40	305 x 110 x 220	4.5
4BT-SCBF6	Small Carrier, Fixed Handle	6	240 x 52 x 40	305 x 110 x 220	6.2
4BT-SCBP6	Small Carrier, Pivot Handle	6	240 x 52 x 40	305 x 110 x 220	6.2
4BT-SCBT	Replacement Tray for Small Carrier Box 5/Box				
4BT-MCBF3	Medium Carrier, Fixed Handle	3	240 x 80 x 40	305 x 137 x 220	5.3
4BT-MCBP3	Medium Carrier, Pivot Handle	3	240 x 80 x 40	305 x 137 x 220	5.3
4BT-MCBF6	Medium Carrier, Fixed Handle	6	240 x 80 x 40	305 x 137 x 220	7.3
4BT-MCBP6	Medium Carrier, Pivot Handle	6	240 x 80 x 40	305 x 137 x 220	7.3
4BT-MCBT	Replacement Tray for Medium Carrier Box 5/Box				

Custom sizes and lead thicknesses available on request

Bright Technologies Ltd
Bri-Tec House, 1 Holbrook Close
Holbrook Commerce Park
Sheffield, S20 3FJ

E-mail: info@britec.net
Tel: +44 (0)114 251 1215

www.britec.net

Version 1.0 May 2026