# Product Datasheet

# SPECT Dispensing Unit

This free standing unit is an economical solution for the sub dispensing of SPECT Isotopes in a grade A air environment.

- Solid surface worktop.
- Vertical grade A air downflow hood.
- Counter sunk shielded waste cupboard to take sharps containers. 3 mm lead shielding as standard.
- Counter sunk dose calibrator housing. Unshielded as standard. Shielding is an optional extra as below.
- 13 Amp socket incorporated into the rear wall of the unit.




## Key Features

- Lead Shielding Options
- Powder Coated Finish

## Optional Extras

### Waste Shielding

- 3 mm lead (6 mm in total).
- 7 mm lead (10 mm in total).

### Dose Calibrator Shielding

- 3 mm lead.
- 7 mm lead.
- 10 mm lead.

## Specifications

| Description | Dimensions (H x W x D) (mm) | Base Unit Dimensions (H) (mm) |
|---|---|---|
| SPECT Dispensing Unit | 2231 x 1000 x 760 approx. | 900 |
| SPECT Dispensing Unit | 2231 x 1200 x 760 approx. | 900 |
| SPECT Dispensing Unit | 2231 x 1500 x 760 approx. | 900 |

Custom sizes and lead thicknesses available on request

**Bright Technologies Ltd**
Bri-Tec House, 1 Holbrook Close
Holbrook Commerce Park
Sheffield, S20 3FJ

**E-mail:** info@britec.net
**Tel:** +44 (0)114 251 1215

**www.britec.net**

BriTec

Version 1.0 May 2026